For Your Convenience: This Cummins File Is Shared By Diesel Parts Direct



YOUR ONE STOP SUPERSTORE FOR DIESEL ENGINE PARTS





## **QSK95**

# Marine Propulsion and Auxiliary Engines for Commercial and Recreational Applications

#### **General Specifications**

ConfigurationV-16 cylinder, 4-stroke dieselAspirationTurbocharged / Aftercooled


Displacement 95.3 L (5813 in<sup>3</sup>)

Bore & Stroke190 X 210 mm (7.48 X 8.27 in)RotationCounterclockwise facing flywheel

Fuel System Modular Common Rail

#### **Product Dimensions and Weight**

**Overall Length** mm (in) Length of Block mm (in) 2598 (102)**Overall Width** 1728 mm (in) (68)Overall Height mm (in) 2362 (93)Weight kg (lb) 13,282 (29,282)Dimensions and weight may vary based on selected engine configuration.



#### **Power Ratings**

	- 5										
Engine Model	Output Power			Engine	Rating	Prelim. Fuel C	Emissions				
	kW	MHP	ВНР	Speed RPM	Definition	Rated Speed L/hr (gal/hr)	ISO* L/hr (gal/hr)	IMO	EPA	EU	RCD
Variable Sp	eed										
QSK95-M	2386**	3245	3200	1500	Continuous	556 (147)	N/A	2	_	_	_
QSK95-M	2685**	3650	3600	1700	Heavy Duty	645 (170)	N/A	2	_	_	_
QSK95-M	2983**	4056	4000	1700	Medium Continuous	703 (186)	N/A	2	_	-	_
QSK95-DM	2983**	4056	4000	1800	Diesel Electric	721 (190)	N/A	2	_	_	_
QSK95-M	3132**	4259	4200	1700	Intermittent	743 (196)	N/A	2	_	_	_
Fixed Speed	d										
QSK95-DM	2625**	3569	3520	1500 (50 Hz)	Prime Power	600 (158)	N/A	2	_	_	_
QSK95-DM	3150**	4283	4224	1800 (60 Hz)	Prime Power	766 (202)	N/A	2	_	_	_

<sup>\*</sup> Average fuel consumption based on ISO 8178 E3 Standard Test Cycle (variable speed models) and ISO 8178 D2 Standard Test Cycle (fixed speed models)

<sup>\*\*</sup> Contact your local Cummins distributor to discuss product details and availability

### **QSK95**

Marine Propulsion and Auxiliary Engines for Commercial and Recreational Applications



The QSK95 is designed to exceed the performance of comparable 20-cylinder high-speed engines, and is far more compact and cost-effective than medium-speed engines at this horsepower. Engineered with premium materials and the latest technologies and design features to ensure the highest performance, the QSK95 has lowest fuel consumption, cleanest emissions and lowest total cost of ownership of any Marine engine in its class. For global ship builders with varied emissions requirements, the QSK95 will meet a variety of emissions standards with a common base engine configuration.

#### **Features and Benefits**

Engine Design – Robust engine block designed for continuous duty operation and long life. Press-in place seals eliminate fluid leaks. Single-piece friction-welded steel piston and rings for exceptional durability. Cummins-designed anti-polish ring improves power cylinder life by minimizing liner wear

Fuel System – High Pressure Common Rail Fuel System provides high injection pressure up to 1800 bar for quiet operation, idle stability, improved low-end torque and reduced emissions. Patented NanoNet™ filtration provides exceptional protection against fuel contamination

**Cooling System** – Two pump, two loop cooling system utilizes a dual impeller, single shaft pump with premium sealing technology. Titanium plate heat exchanger provides superior durability with minimal maintenance requirements

**Exhaust System** – Dry shielded exhaust manifold meets SOLAS requirements, while reducing fuel consumption and improving performance

**Air System** – Cummins turbochargers optimized for marine applications. Two-stage aftercooling for improved fuel efficiency, reduced emissions and enhanced durability

**Lubrication System** – Spin-on filters standard or optional ELIMINATOR™ self-cleaning oil filtration system to reduce maintenance time and cost.

Pre-lube pump protects engine from damage due to dry starts

**Electronics** – 24v electronics feature new lead-free Cummins ECM to monitor operating parameters, while providing diagnostics and complete engine protection. Customer interface box for all vessel connections to reduce installation complexity

**Certifications** – Complies with IMO Tier II emissions regulations. Engineered to meet the International Association of Classification Societies (IACS) and SOLAS requirements. Contact your local Cummins distributor for the latest certifications available

#### **Optional Equipment**

- SAE B accessory drive
- Turbine air starters
- C Command Elite Plus monitoring and display panels
- Fully integrated type approved alarm and safety system



Cummins Inc. 4500 Leeds Avenue – Suite 301 Charleston, SC 29405-8539 U.S.A.