For Your Convenience: This File Is Shared By Diesel Parts Direct



YOUR ONE STOP SUPERSTORE FOR DIESEL ENGINE PARTS





Model 18400-0050

SELF-PRIMING PUMP FEATURES

Body: Bronze

Impeller: Jabsco Neoprene Compound

Shaft: 316 Stainless Steel


Shaft Seal: Lip Type
Ports: 3/4" NPT
Weight: 6 lb (approx.)

APPLICATION


Marine Engine Cooling

FOR ENGINE MODELS

ONAN MDJ-C MDJ-F



Model 18400-0050



INSTALLATION INSTRUCTIONS

Engine shaft with drive tang, make sure flange seats squarely on mounting surface and bolt to engine. Connect inlet and outlet fittings using pipe compound to seal threads.


OPERATING INSTRUCTIONS

Pump will self-prime at low or high speeds. Make sure scoop and inlet line are clear and all connections airtight. Do not run pump dry for more than 30 seconds. Lack of water flow may damage impeller. To drain pump, loosen end cover screws.


SERVICE INSTRUCTIONS

Impeller Replacement: Remove end cover and gasket. Pull impeller out by grasping hub or blades with pliers. Replace impeller, gasket and end cover. A light coating of grease in impeller bore will aid priming on dry start up. (Use correct Jabsco gasket, a thicker or thinner gasket may cause impeller damage.) Standard gasket in 0.010" thick.

Major Repair: Remove pump from engine to replace seal, bearings or shaft. To disassemble pump, remove end cover, gasket and impeller ar outlined above. Press on impeller end of shaft to remove shaft and bearing



assembly. Remove cam and wearplate assembly. Use screw driver to pry bearing seal out of bearing bore. Press shaft seal out towards impeller bore. Replace all worn parts. When installing coupling, support splined end of shaft. Press bearing seal in bearing bore with lip towards bearing. Press shaft and bearing assembly into bearing bore. Press adaptor ring into body. Install slinger on shaft. Install seal spacer in seal cavity. Install O-ring in seal bore. Press seal in seal cavity with lip facing toward impeller bore. Apply a thin coat of sealant to top of cam and cam screw threads, install wearplate and cam assembly. (Be sure cam is flush with end cover surface.) Secure with screw. Lubricate impeller bore, install impeller. Lubricate impeller face, install gasket and end cover and secure with screws.



PARTS LIST

- A. 1. 0 = 1.0 1			
Key	Description	Qty.	Part No.
1	Screw (End Cover)	6	91002-0020
2	End Cover	1	11830-0000
*3	Gasket	1	5212-0000
*4	Impeller	1	1210-0001
*6	Seal (Shaft)	1	92700-0060
*7	O-Ring [†]	1	92000-0210
8	Screw (Cam)	1	91003-0090
9	Cam Wearplate Assembly	/ 1	5211-0000
10	Seal Spacer	1	3166-0000
11	Body	1	
12	Adaptor Ring	1	3376-0000
13	Slinger	1	3286-0000
14	Shaft	1	18404-0000
15	Bearing Seal	1	92700-0060
16	Ball Bearing	1	92600-0130
17	Bearing Spacer	2	3383-0000
	Service Kit		90033-0001

- * Parts contained in Service Kit.
- [†] O-ring used only in pumps manufactured prior to June, 1993.

Jabsco



U.S.A. Jabsco 1485 Dale Way, P.O. Box 2158 Costa Mesa, CA 92628-2158 Tel: (714) 545-8251 Fax: (714) 957-0609 UNITED KINGDOM Jabsco Bingley Road, Hoddesdon Hertfordshire EN11 OBU Tel: +44 (0) 1992 450145 Fax: +44 (0) 1992 467132



CANADA Fluid Products Canada 55 Royal Road Guelph, Ontario N1H 1T1 Tel: (519) 821 -1900 Fax: (519) 821-2569 THE PRODUCTS DESCRIBED HEREIN ARE SUBJECT TO THE JABSCO ONE YEAR LIMITED WARRANTY, WHICH IS AVAILABLE FOR YOUR INSPECTION UPON REQUEST.

Form: 43000-0624

JAPAN NHK Jabsco Company Ltd. 3-21-10, Shin-Yokohama Kohoku-Ku, Yokohama, 222 Tel: 045-4758906 Fax: 045-475-8908 GERMANY
Jabsco GmbH
Oststrasse 28
22844 Norderstedt
Tel: +49-40-53 53 73 -0
Fax: +49-40-53 53 73 -11